

SIMATIC SD memory card 2 GB Secure Digital Card for For devices with corresponding Slot Further information, Quantity and content: see technical data



General information	
Product type designation	SD memory card
Control elements	
Frame size/design	
<ul style="list-style-type: none"> • Standard 	Yes; Typically 10 000 insertion cycles
<ul style="list-style-type: none"> • Flat 	Yes
Installation type/mounting	
Mounting position	Any, dependent on target device
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	3.3 V; Max 3.6 V
Input current	
Current consumption (rated value)	100 mA; Typical, maximum value
Memory	
Type of memory	Secure Digital memory card

Memory size	2 048 Mbyte; Larger internal memory
Transmission rate for reading, max.	1.6 Mbit/s; Minimum, typical for newly formatted memory
Transmission rate for writing, max.	1.6 Mbit/s; Minimum, typical for newly formatted memory
Wear leveling (distributed writing)	Yes; > 100 000 write/read cycles per cell and > 3 000 000 write/read cycles per card
Write protection switch	Yes; Effectiveness depends on the device

Interfaces

Device-side interface	
<ul style="list-style-type: none"> • Number of pins device-side 	9

Standards, approvals, certificates

CE mark	Yes
UL approval	Yes
cULus	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
RoHS conformity	Yes
China RoHS compliance	Yes
Marine approval	Yes; Passive component, therefore dependent on target device

Use in hazardous areas

<ul style="list-style-type: none"> • ATEX Zone 2 	Yes; Always comply with the operating instructions of the target device.
<ul style="list-style-type: none"> • ATEX Zone 22 	Yes; Always comply with the operating instructions of the target device.
<ul style="list-style-type: none"> • IECEx Zone 2 	Yes; Always comply with the operating instructions of the target device.
<ul style="list-style-type: none"> • IECEx Zone 22 	Yes; Always comply with the operating instructions of the target device.
<ul style="list-style-type: none"> • cULus Class I Zone 2, Division 2 	Yes; Always comply with the operating instructions of the target device.
<ul style="list-style-type: none"> • FM Class I Division 2 	Yes; Always comply with the operating instructions of the target device.

Marine approval

<ul style="list-style-type: none"> • Germanischer Lloyd (GL) 	Yes; Always comply with the operating instructions of the target device.
<ul style="list-style-type: none"> • American Bureau of Shipping (ABS) 	Yes; Always comply with the operating instructions of the target device.
<ul style="list-style-type: none"> • Bureau Veritas (BV) 	Yes; Always comply with the operating instructions of the target device.
<ul style="list-style-type: none"> • Det Norske Veritas (DNV) 	Yes; Always comply with the operating instructions of the target device.
<ul style="list-style-type: none"> • Lloyds Register of Shipping (LRS) 	Yes; Always comply with the operating instructions of the target device.
<ul style="list-style-type: none"> • Nippon Kaiji Kyokai (Class NK) 	Yes; Always comply with the operating instructions of the target device.

• Polski Rejestr Statkow (PRS)	Yes; Always comply with the operating instructions of the target device.
• Chinese Classification Society (CCS)	Yes; Always comply with the operating instructions of the target device.
• Compass working clearance	5 m

Ambient conditions

Suited for indoor use	Yes
Suited for outdoor use	Yes; Possible under certain conditions
Ambient temperature during operation	
• min.	-30 °C
• max.	60 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	80 °C
Relative humidity	
• Operation, max.	95 %
• Condensation permissible	No; Condensation not permissible

Operating systems

pre-installed operating system	
• Windows CE	No; Preinstalled system files
Runs under operating system	
• Windows CE	Yes
• Windows Vista	Yes
• Windows XP	Yes
• Windows 7	Yes
• Windows 8	Yes
• Windows 10	Yes
• Linux	No
• other	Yes; Card must not be formatted!

Mechanics/material

Enclosure material (front)	
• Plastic	Yes; Gold contacts
Enclosure color (front)	
	RAL 6034 (color deviation possible)
Service life	
• Number of operating cycles, keys	10; Min. data storage without loss (in years)

Dimensions

Width	24 mm
Height	32 mm
Thickness	2.1 mm

Weights

Weight without packaging	3 g
Weight incl. packaging	6 g

Scope of supply

Delivery quantity in pieces	1
-----------------------------	---

Other

Merchandise	No
Manufacturer name	SIEMENS AG
Manufacturer's address	Gleiwitzerstraße 555, 90475 Nuremberg, Germany
Target devices	Especially for KTP Mobile Panels 2nd Generation, MP377 and Comfort Panels, but also for all other panels (other than Classic Panels) and PCs with suitable slot
Note:	Not suitable for MP177, MP277, Mobile Panel 277, OP77, TP/OP177, TP/OP277 and Mobile Panel 177

Usable in the following products

<ul style="list-style-type: none"> • Product 2 • Product 3 • Product 4 • Product 5 • Product 6 	<p>6AV2124-1*</p> <p>6AV2124-2DC01-0AX0</p> <p>6AV2125-2G*</p> <p>6AV2125-2J*</p> <p>6AV6644*</p>
---	---

last modified: 02/05/2020