



SCALANCE XC208 manageable layer 2 IE Switch; 8x 10/100 Mbit/s RJ45 ports; 1x console port; Diagnostic LED; Redundant power supply; Temp. range -40°C to +70 °C Mounting: Standard Mounting Rail/S7 Profile Rail/Wall Office redundancy functions features (RSTP, VLAN ,...); PROFINET IO device Ethernet/IP-compliant C-PLUG shaft;

Product type designation	SCALANCE XC208
Transfer rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Interfaces / for communication / Integrated	
Number of electrical connections	
• for network components or terminal equipment	8; RJ45
Number of 10/100 Mbit/s RJ45 ports / Integrated	
• with securing collar	8
Interfaces / other	
Number of electrical connections	
• for operator console	1
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
Type of electrical connection	
• for operator console	RJ11
• for signaling contact	2-pole terminal block
• for power supply	4-pole terminal block

design of the removable storage	
• C-PLUG	Yes
Signal inputs/outputs	
Operating voltage / of the signaling contacts	
• at DC / Rated value	24 V
Operating current / of the signaling contacts	
• at DC / maximum	0.1 A
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage	
• external	24 V
• external / minimum	9.6 V
• external / maximum	31.2 V
Supply voltage / 4 / Rated value	
• Consumed current / 4 / at rated supply voltage / maximum	0.175 A
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	2.5 A / 125 V
Consumed current / maximum	0.35 A
Power loss [W]	
• at DC / at 24 V	4.2 W
Ambient conditions	
Ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20
Design, dimensions and weights	
Design	compact
Width	60 mm
Height	147 mm
Depth	125 mm
Net weight	0.52 kg
Material / of the enclosure	Polycarbonate (PC-GF10) / pressure die cast aluminum
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes
• S7-300 rail mounting	Yes

- S7-1500 rail mounting

Yes

Product features, product functions, product components / general

Cascading in the case of a redundant ring / at reconfiguration time of $< \sim 0.3 \text{ s}$	50
Cascading in cases of star topology	any (depending only on signal propagation time)
Product function / QoS according to DSCP	Yes
Product feature	
• Cut Through switching method	No
• Store & Forward switching method	Yes

Product functions / management, configuration, engineering

Product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• Configuration with STEP 7	Yes
• RMON	Yes
• SMTP server	No
• Port mirroring	Yes
• multiport mirroring	Yes
• CoS	Yes
• PROFINET IO diagnosis	Yes
PROFINET conformity class	B
Product function / switch-managed	Yes
Telegram length / for Ethernet / maximum	1632 byte
Protocol / is supported	
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• BOOTP	No
• GMRP	Yes
• DCP	Yes
• LLDP	Yes
• EtherNet/IP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
• IGMP (snooping/querier)	Yes
Identification & maintenance function	
• I&M0 - device-specific information	Yes

- I&M1 – higher-level designation/location designation

Yes

Product functions / Diagnostics

Product function

- Port diagnostics
- Statistics Packet Size
- Statistics packet type
- Error statistics
- SysLog

Yes

Yes

Yes

Yes

Yes

Product functions / VLAN

Product function

- VLAN - port based
- VLAN - protocol-based
- VLAN - IP-based

Yes

No

No

Number of VLANs / maximum

257

Number of VLANs - dynamic / maximum

257

Protocol / is supported / GVRP

Yes

Product functions / DHCP

Product function

- DHCP server
- DHCP client
- DHCP Option 82
- DHCP Option 66
- DHCP Option 67

Yes

Yes

Yes

Yes

Yes

Product functions / redundancy

Product function

- of the PROFINET IO device / is supported / PROFINET system redundancy (S2)
- Ring redundancy
- High Speed Redundancy Protocol (HRP)
- high speed redundancy protocol (HRP) with redundancy manager
- high speed redundancy protocol (HRP) with standby redundancy

Yes

Yes

Yes

Yes

Yes

Protocol / is supported / Media Redundancy Protocol (MRP)

Yes

Product function

- media redundancy protocol (MRP) with redundancy manager
- of the PROFINET IO device / is supported / H-Sync forwarding

Yes

Yes

• redundancy procedure STP	Yes
• redundancy procedure RSTP	Yes
• redundancy procedure MSTP	Yes
• Parallel Redundancy Protocol (PRP)/operation in the PRP-network	Yes
• Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No
• Passive listening	Yes
Protocol / is supported	
• LACP	Yes

Product functions / Security

Product function	
• IEEE 802.1x (radius)	Yes
• Broadcast/Multicast/Unicast Limiter	Yes
• broadcast blocking	Yes
Protocol / is supported	
• SSH	Yes
• SSL	Yes

Product functions / time

Product function	
• SICLOCK support	Yes
• NTP-client	Yes
• SNTP client	Yes
Protocol / is supported	
• NTP	Yes
• SNTP	Yes

System modification during operation

Product function / configuration in RUN via CiR/H-CiR	Yes
---	-----

Standards, specifications, approvals

Security for industrial automation and control systems / acc. to IEC 62443-4-2:2019	Yes
MTBF	48 y

Standards, specifications, approvals / CE

Certificate of suitability / CE marking	Yes
Product conformity / according to EMC-guideline	2014/30/EU
Standard	
• for EMC interference emission	EN 61000-6-4, EN 50121-4
• for immunity to EMI	EN 61000-6-2, EN 50121-4
Certificate of suitability / RoHS conformity	Yes; 2011/65/EU

Standards, specifications, approvals / hazardous environments

Certificate of suitability

- | | |
|----------------------------------|--|
| • ATEX | Yes; EN 60079-0, EN 60079-15 |
| • for ATEX / as marking | II 3 G Ex nA II T4 Gc |
| • for ATEX / as certificate | KEMA 07ATEX0145 X |
| • IECEx | Yes; IEC 60079-0, IEC 60079-15 |
| • for IECEx / as marking | Ex nA II T4 Gc |
| • for IECEx / as certificate | IECEx DEK 14.0025X |
| • for cULus HazLoc / as marking | CL1, DIV2, Group A,B,C,D T4, CL1, Zone 2, Group IIC, T4 |
| • for cULus HazLoc / as File Nr. | E240480 (NWHP, NWHP7) |
| • FM registration | Yes; FM class 3600:2011, FM class 3611:2004, FM class 3810:2005, ANSI/ISA-61010-1:2004 |
| • for FM / as marking | CL1, DIV2, group A,B,C,D T4, CL1, Zone 2, group IIC, T4 Ta: -40 °C +70 °C |
| • for FM / as certificate | FM16US0205X |

Standards, specifications, approvals / other

Certificate of suitability

- | | |
|---|-----------------------|
| • Railway application in accordance with EN 50121-4 | Yes |
| • Regulatory Compliance Mark (RCM) | Yes |
| • for UL 61010-2-201 / as File Nr. | E85972 (NRAQ, NRAQ7) |
| • for UL 60950-1 / as File Nr. | E115352 (NWGQ, NWGQ7) |
| • EAC approval | Yes |

Standards, specifications, approvals / marine classification

Marine classification association

- | | |
|---|-----|
| • American Bureau of Shipping Europe Ltd. (ABS) | Yes |
| • Bureau Veritas (BV) | Yes |
| • DNV GL | Yes |
| • Korean Register of Shipping (KRS) | Yes |
| • Lloyds Register of Shipping (LRS) | Yes |
| • Nippon Kaiji Kyokai (NK) | Yes |
| • Polski Rejestr Statkow (PRS) | Yes |
| • Royal Institution of Naval Architects (RINA) | Yes |

accessories

- | | |
|---------------------------------------|-----|
| Product extension / optional / C-PLUG | Yes |
|---------------------------------------|-----|

Further information / Internet-Links

Internet-Link

- | | |
|---|---|
| • to website: Selector SIMATIC NET SELECTION TOOL | http://www.siemens.com/snst |
| • to website: Industrial communication | http://www.siemens.com/simatic-net |

- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

05/13/2020