

SIMATIC S7-1500 Digital output module, DQ16x24 V DC/0.5A BA, 16 channels in groups of 8, 4 A per group; Delivery incl. front connector Push-in



General information	
Product type designation	DQ 16x24VDC/0.5A BA
HW functional status	FS01
Firmware version	V1.0.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	No
<ul style="list-style-type: none"> <li>Prioritized startup</li> </ul>	Yes
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated as of version</li> </ul>	V13 / V13
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated as of version</li> </ul>	V5.5 SP3 / -
<ul style="list-style-type: none"> <li>PROFIBUS as of GSD version/GSD revision</li> </ul>	V1.0 / V5.1
<ul style="list-style-type: none"> <li>PROFINET as of GSD version/GSD revision</li> </ul>	V2.3 / -
Operating mode	
<ul style="list-style-type: none"> <li>DQ</li> </ul>	Yes
<ul style="list-style-type: none"> <li>DQ with energy-saving function</li> </ul>	No
<ul style="list-style-type: none"> <li>PWM</li> </ul>	No

- Oversampling
- MSO

No  
Yes

### Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes; through internal protection with 7 A per group

### Input current

Current consumption, max.	30 mA
---------------------------	-------

### Output voltage

Rated value (DC)	24 V
------------------	------

### Power

Power available from the backplane bus	1.15 W
--	--------

### Power loss

Power loss, typ.	2.2 W
------------------	-------

### Digital outputs

Type of digital output	Transistor
Number of digital outputs	16
Current-sourcing	Yes
Digital outputs, parameterizable	No
Short-circuit protection	Yes
<ul style="list-style-type: none"> <li>• Response threshold, typ.</li> </ul>	1 A
Limitation of inductive shutdown voltage to	L+ (-53 V)
Controlling a digital input	Yes

### Switching capacity of the outputs

- with resistive load, max. 0.5 A
- on lamp load, max. 5 W

### Load resistance range

- lower limit 48  $\Omega$
- upper limit 12 k $\Omega$

### Output voltage

- for signal "1", min. L+ (-0.8 V)

### Output current

- for signal "1" rated value 0.5 A
- for signal "1" permissible range, max. 0.5 A
- for signal "0" residual current, max. 0.5 mA

### Output delay with resistive load

- "0" to "1", max. 100  $\mu$ s
- "1" to "0", max. 500  $\mu$ s

### Parallel switching of two outputs

• for logic links	Yes
• for uprating	No
• for redundant control of a load	Yes
<b>Switching frequency</b>	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz; According to IEC 60947-5-1, DC-13
• on lamp load, max.	10 Hz
<b>Total current of the outputs</b>	
• Current per channel, max.	0.5 A; see additional description in the manual
• Current per group, max.	4 A; see additional description in the manual
• Current per module, max.	8 A; see additional description in the manual
<b>Cable length</b>	
• shielded, max.	1 000 m
• unshielded, max.	600 m
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	No
Substitute values connectable	No
<b>Alarms</b>	
• Diagnostic alarm	No
• Maintenance interrupt	No
<b>Diagnostic messages</b>	
• Monitoring the supply voltage	No
• Wire-break	No
• Short-circuit	No
• Group error	No
<b>Diagnostics indication LED</b>	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green LED
• Channel status display	Yes; green LED
• for channel diagnostics	No
• for module diagnostics	No
<b>Potential separation</b>	
<b>Potential separation channels</b>	
• between the channels	No
• between the channels, in groups of	8
• between the channels and backplane bus	Yes
<b>Isolation</b>	
Isolation tested with	707 V DC (type test)
<b>Standards, approvals, certificates</b>	

Suitable for safety functions	No
-------------------------------	----

### Ambient conditions

Altitude during operation relating to sea level	
---	--

- Installation altitude above sea level, max. 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual

### Dimensions

Width	25 mm
-------	-------

Height	147 mm
--------	--------

Depth	129 mm
-------	--------

### Weights

Weight, approx.	230 g
-----------------	-------

### Other

Note:	Supplied incl. 40-pole push-in front connectors
-------	---

<b>last modified:</b>	03/16/2020
-----------------------	------------