

product type designation



CP 1542-5

Communications processor CP 1542-5 for connection of SIMATIC S7-1500 to PROFIBUS DP, DPV1 master or DP slave, S7 and PG/OP communication, time-of-day synchronization, diagnostics, reduced quantity structure

transfer rate	
transfer rate	
<ul style="list-style-type: none"> at the 1st interface / acc. to PROFIBUS 	9.6 kbit/s ... 12 Mbit/s
interfaces	
number of interfaces / acc. to Industrial Ethernet	0
number of electrical connections	
<ul style="list-style-type: none"> at the 1st interface / acc. to PROFIBUS 	1
type of electrical connection	
<ul style="list-style-type: none"> at the 1st interface / acc. to PROFIBUS 	9-pin Sub-D socket (RS485)
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	15 V
relative symmetrical tolerance / at DC	
<ul style="list-style-type: none"> at 15 V 	3 %
consumed current	
<ul style="list-style-type: none"> from backplane bus / at DC / at 15 V / typical 	0.1 A
power loss [W]	1.5 W
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> for vertical installation / during operation 	0 ... 40 °C
<ul style="list-style-type: none"> for horizontally arranged busbars / during operation 	0 ... 60 °C
<ul style="list-style-type: none"> during storage 	-40 ... +70 °C
<ul style="list-style-type: none"> during transport 	-40 ... +70 °C
relative humidity	
<ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-1500 single width
width	35 mm
height	142 mm
depth	129 mm
net weight	0.27 kg
fastening method	
<ul style="list-style-type: none"> S7-1500 rail mounting 	Yes
product features, product functions, product components / general	
number of units	
<ul style="list-style-type: none"> per CPU / maximum 	8

<ul style="list-style-type: none"> • note 	depending on CPU type
performance data / PROFIBUS DP	
service / as DP master <ul style="list-style-type: none"> • DPV1 	Yes
number of DP slaves <ul style="list-style-type: none"> • on DP master / operable 	32
data volume <ul style="list-style-type: none"> • of the address range of the inputs / as DP master / total • of the address range of the outputs / as DP master / total • of the address range of the inputs / per DP slave • of the address range of the outputs / per DP slave 	2048 byte 2048 byte 244 byte 244 byte
service / as DP slave <ul style="list-style-type: none"> • DPV0 • DPV1 	Yes Yes
data volume <ul style="list-style-type: none"> • of the address range of the inputs / as DP slave / total • of the address range of the outputs / as DP slave / total 	240 byte 240 byte
performance data / S7 communication	
number of possible connections / for S7 communication <ul style="list-style-type: none"> • maximum 	16; depending on the system upper limit
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	16
performance data / telecontrol	
protocol / is supported <ul style="list-style-type: none"> • TCP/IP 	No
product functions / management, configuration, engineering	
configuration software <ul style="list-style-type: none"> • required 	STEP 7 Professional V12 SP1 (TIA Portal) or higher
identification & maintenance function <ul style="list-style-type: none"> • I&M0 - device-specific information • I&M1 – higher level designation/location designation 	Yes Yes
product functions / diagnostics	
product function / web-based diagnostics	Yes; via S7-1500 CPU
product functions / time	
product function / pass on time synchronization	Yes
standards, specifications, approvals / hazardous environments	
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
further information / internet-Links	
Internet-Link <ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support 	http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be

considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

8/3/2021 