



<b>Product description</b>			
Standard	Industrial standard (11 mm)	Industrial standard (11 mm)	
Construction type	B	B	
Description	P11 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and protective circuit (diode)	P11 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and TVS protective circuit (transil)	
Housing colour	transparent	transparent	
Number of contacts	2+PE	2+PE	
Order no.	<b>KB132D54T9</b>	<b>KB132T54T9</b>	
Other options on request	led colour red led colour green	order no. <b>KB132D57T9</b> order no. <b>KB132T57T9</b>	
Cable gland	PG9 (M16x1,5 on request)	PG9 (M16x1,5 on request)	
Max. conductor size	1,5mm <sup>2</sup> without splice/terminal	1,5mm <sup>2</sup> without splice/terminal	
<b>Drawing</b>			
<b>Technical data</b>			
Pin dimension	6,3 x 0,8mm	6,3 x 0,8mm	
Voltage	24 V DC	24 V AC/DC	
Rated current max.	4 A	4 A	
Suppressor	diode 1A 1000V	TVS Vbr max.=37,8V Peak=400W	
LED colour	yellow	yellow	
Contact resistance	15mΩ max.	15mΩ max.	
Overvoltage category	III	III	
Type of termination	screw M3	screw M3	
Contact screw torque	max. 0,5 N/m	max. 0,5 N/m	
Suitable cables	5 mm to 7 mm diameter	5 mm to 7 mm diameter	
Mounting	central screw M3x32,5	central screw M3x32,5	
<b>Material</b>			
Contact holder material	PA6 GF	PA6 GF	
Housing material	PA12	PA12	
<b>Environmental conditions</b>			
Protection class (EN 60529)	IP 65 when correctly assembled	IP 65 when correctly assembled	
Pollution severity (EN 60664-1)	3	3	
Temperature range	-20°C to + 80°C	-20°C to + 80°C	
<b>Inflammability class</b>			
Contact holder	HB - UL 94	HB - UL 94	
Housing	HB - UL 94	HB - UL 94	
<b>Packaging</b>			
Packaging unit / Weight approx.	100 pieces / 2,5Kg	100 pieces / 2,5Kg	
Box dimensions	29 x 15 x 18 cm	29 x 15 x 18 cm	
<b>Other accessories options</b>			
to be ordered separately see pages 171-175	NBR flat gasket 100 pcs in bag Stainless steel screw 100 pcs in bag	NBR flat gasket 100 pcs in bag Stainless steel screw 100 pcs in bag	