

Valve Connectors KA1 series

SELF - ASSEMBLY CABLE



EN175301-803	EN175301-803	EN175301-803	EN175301-803
A	A	A	A
P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and TVS protective circuit (transil)	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and TVS protective circuit (transil)	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and RC protective circuit	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and RC protective circuit
transparent	transparent	transparent	transparent
2+PE	2+PE	2+PE	2+PE
KA132T54T9	KA132T54T1	KA132C54T9	KA132C54T1
order no. KA132T57T9	order no. KA132T57T1		
order no. KA132T5AT9	order no. KA132T5AT1		
PG9 (M16x1,5 on request)	PG11	PG9 (M16x1,5 on request)	PG11
1,5mm ² without splice/terminal	1,5mm ² without splice/terminal	1,5mm ² without splice/terminal	1,5mm ² without splice/terminal
6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm
24 V AC/DC	24 V AC/DC	24 V AC/DC	24 V AC/DC
4 A	4 A	4 A	4 A
TVS Vbr max.=37,8V Peak=400W	TVS Vbr max.=37,8V Peak=400W	Filter RC C=0,1 µF R=100 Ω	Filter RC C=0,1 µF R=100 Ω
yellow	yellow	yellow	yellow
15mΩ max.	15mΩ max.	15mΩ max.	15mΩ max.
III	III	III	III
screw M3	screw M3	screw M3	screw M3
max. 0,5 N/m	max. 0,5 N/m	max. 0,5 N/m	max. 0,5 N/m
5 mm to 7 mm diameter	6 mm to 9 mm diameter	5 mm to 7 mm diameter	6 mm to 9 mm diameter
central screw M3x32,5	central screw M3x32,5	central screw M3x32,5	central screw M3x32,5
PA6 GF	PA6 GF	PA6 GF	PA6 GF
PA12	PA12	PA12	PA12
IP 65 when correctly assembled	IP 65 when correctly assembled	IP 65 when correctly assembled	IP 65 when correctly assembled
3	3	3	3
-20°C to + 80°C	-20°C to + 80°C	-20°C to + 80°C	-20°C to + 80°C
HB - UL 94	HB - UL 94	HB - UL 94	HB - UL 94
HB - UL 94	HB - UL 94	HB - UL 94	HB - UL 94
100 pieces / 2,5Kg	100 pieces / 2,5Kg	100 pieces / 2,5Kg	100 pieces / 2,5Kg
29 x 15 x 18 cm	29 x 15 x 18 cm	29 x 15 x 18 cm	29 x 15 x 18 cm
NBR flat gasket 100 pcs in bag	NBR flat gasket 100 pcs in bag	NBR flat gasket 100 pcs in bag	NBR flat gasket 100 pcs in bag
Silicon profile gasket 100 pcs in bag	Silicon profile gasket 100 pcs in bag	Silicon profile gasket 100 pcs in bag	Silicon profile gasket 100 pcs in bag
Stainless steel screw 100 pcs in bag	Stainless steel screw 100 pcs in bag	Stainless steel screw 100 pcs in bag	Stainless steel screw 100 pcs in bag

Form A - EN 175301-803 (DIN43650) / ISO 4400



Form A - EN 175301-803 (DIN43650) / ISO 4400

Product description			
Standard		EN175301-803	EN175301-803
Construction type		A	A
Description		P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED)	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED)
Housing colour		transparent	transparent
Number of contacts		2+PE	2+PE
Order no.		KA132L34T9	KA132L35T9
Other options on request	led colour red	order no. KA132L37T9	order no. KA132L38T9
	led colour green	order no. KA132L3AT9	order no. KA132L3BT9
Cable gland		PG9 (M16x1,5 on request)	PG9 (M16x1,5 on request)
Max. conductor size		1,5mm ² without splice/terminal	1,5mm ² without splice/terminal
Drawing			
Technical data			
Pin dimension		6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm
Voltage		24 V AC/DC	115 V AC/DC
Rated current max.		8 A	8 A
LED colour		yellow	yellow
Contact resistance		15mΩ max.	15mΩ max.
Overvoltage category		III	III
Type of termination		screw M3	screw M3
Contact screw torque		max. 0,5 N/m	max. 0,5 N/m
Suitable cables		5 mm to 7 mm diameter	5 mm to 7 mm diameter
Mounting		central screw M3x32,5	central screw M3x32,5
Material			
Contact holder material		PA6 GF	PA6 GF
Housing material		PA12	PA12
Environmental conditions			
Protection class (EN 60529)		IP 65 when correctly assembled	IP 65 when correctly assembled
Pollution severity (EN 60664-1)		3	3
Temperature range		-20°C to + 80°C	-20°C to + 80°C
Inflammability class			
Contact holder		HB - UL 94	HB - UL 94
Housing		HB - UL 94	HB - UL 94
Packaging			
Packaging unit / Weight approx.		100 pieces / 2,5Kg	100 pieces / 2,5Kg
Box dimensions		29 x 15 x 18 cm	29 x 15 x 18 cm
Other accessories options			
to be ordered separately see pages 171-175		NBR flat gasket 100 pcs in bag	NBR flat gasket 100 pcs in bag
		Silicon profile gasket 100 pcs in bag	Silicon profile gasket 100 pcs in bag
		Stainless steel screw 100 pcs in bag	Stainless steel screw 100 pcs in bag