

SIMATIC S7-1200, DIGITAL INPUT SM 1221, 8DI, 24V DC,
SINK/SOURCE INPUT



Supply voltage	
24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
from backplane bus 5 V DC, max.	105 mA
Digital inputs	
<ul style="list-style-type: none"> from load voltage L+ (without load), max. 	4 mA; per channel
Output voltage	
Power supply to the transmitters	
<ul style="list-style-type: none"> present 	Yes
Power losses	
Power loss, typ.	1.5 W
Digital inputs	
Number of digital inputs	8
<ul style="list-style-type: none"> In groups of 	2
Input characteristic curve in accordance with IEC 61131, type 1	Yes

Number of simultaneously controllable inputs	
all mounting positions	
— up to 40 °C, max.	8
horizontal installation	
— up to 40 °C, max.	8
— up to 50 °C, max.	8
vertical installation	
— up to 40 °C, max.	8
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	5 V DC at 1 mA
• for signal "1"	15 VDC at 2.5 mA
Input current	
• for signal "0", max. (permissible quiescent current)	1 mA
• for signal "1", min.	2.5 mA
• for signal "1", typ.	4 mA; Typical
Input delay (for rated value of input voltage)	
for standard inputs	
— Parameterizable	Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four
for interrupt inputs	
— Parameterizable	Yes
Cable length	
• Cable length, shielded, max.	500 m
• Cable length unshielded, max.	300 m
Digital outputs	
Number of digital outputs	0
short-circuit protection	No
Interrupts/diagnostics/status information	
Alarms	
• Alarms	Yes
• Diagnostic alarm	Yes
Diagnostic messages	
• Diagnostic functions	Yes
• Monitoring the supply voltage	Yes
Diagnostics indication LED	
• for status of the inputs	Yes
• for maintenance	Yes
• Status indicator digital input (green)	Yes
Galvanic isolation	
Galvanic isolation digital inputs	

- between the channels, in groups of 2

Degree and class of protection

Degree of protection to EN 60529	
• IP20	Yes

Standards, approvals, certificates

CE mark	Yes
RCM (formerly C-TICK)	Yes
FM approval	Yes

Climatic and mechanical conditions for storage and transport

Climatic conditions for storage and transport

Free fall

— Drop height, max. (in packaging)	0.3 m; five times, in dispatch package
------------------------------------	--

Temperature

— Permissible temperature range	-40 °C to +70 °C
---------------------------------	------------------

Air pressure acc. to IEC 60068-2-13

— Permissible air pressure	1080 to 660 hPa
----------------------------	-----------------

Relative humidity

— Permissible range (without condensation) at 25 °C	95 %
---	------

Mechanical and climatic conditions during operation

Climatic conditions in operation

Temperature

— Permissible temperature range	-20 °C to +60 °C horizontal mounting, -20 °C to 50 °C vertical mounting, 95% humidity, non-condensing
— Permissible temperature change	5°C to 55°C, 3°C / minute

Connection method

required front connector	Yes
--------------------------	-----

Mechanics/material

Type of housing (front)	
• plastic	Yes

Dimensions

Width	45 mm
Height	100 mm
Depth	75 mm

Weights

Weight, approx.	170 g
last modified:	14.10.2014