

**017-523766**

RT switches are used in general industrial and marine sectors. The RT single pressure switches series consist of a variety of ordinary controls including neutral zone pressure switches, safety pressure...

- > **Product specifications**
- > **Dimensions**
- > **Associated products (1)**
- > **Literature (18)**
- > **Switch Selector**

- > **Code number selector**
- > **Photos (1)**
- > **Approvals & certificates (24)**
- > **Contact**



0

Characteristic	Value
Type	RT200
Weight	0.850 Kg
Ambient temperature [°C]	-50 - 70 °C
Ambient temperature [°F]	-58 - 158 °F
Ambient temperature [°C]	-50 - 70 °C
Ambient temperature range [°F]	-58 - 158 °F
Ammonia application	No
Approval	BV, CCC, CE, DNV, GL, KRS, NKK, RINA, RMRS
Contact function	SPDT
Contact rating	AC1=10 A, 400 V
Contact rating	AC15=3 A, 400 V
Contact rating	AC3=4 A, 400 V
Contact rating	DC13=12 W, 220 V
Contact rating	LR=28 A, 400 V
Differential [bar]	0,25 - 1,20 bar
Differential [psi]	3,60 - 17,40 psi
EAN	5702423120918
Electrical connection size	2xPg 13.5
Electrical specification standard	EN 60947-4/-5
Enclosure rating	IP66
Max. test pressure [bar] Pe	25,0 bar
Max. Working Pressure [bar]	22,0 bar
Max. Working Pressure [psig]	320 psig
Max. working pressure [bar] Pe	22,0 bar
Max. working pressure [psig] Pe	320,0 psig
Packing format	Multi pack
Pressure connection	G 3/8
Pressure connection standard	ISO228-1
Pressure Male/Female	Male
Product description	Pressure Control
Product Design class	B
Quantity per packing format	15 PC
Regulation range [bar] Pe	0,20 - 6,00 bar
Regulation range [psig] Pe	2,90 - 87,00 psig
Reset function	AUTO